

POWER MAXED AIR-CON REFRESH (CITRUS)

Page: 1

Compilation date: 01/06/2018

Revision date: 05/04/19

Revision No: 3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: POWER MAXED AIR-CON REFRESH

Product code: AIRCONBOMB

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Automotive Brands

3B Wellington Road

Waterloo Park
Bidford on Avon
Warwickshire

B50 4JH

United Kingsom

Tel: 01789 330668

Email: sales@automotivebrands.co.uk

1.4. Emergency telephone number

Emergency tel: 01789 330668

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Aerosol 1: H222; Aquatic Chronic 3: H412; -: EUH208; -: H229

Most important adverse effects: Contains citral, limonene. May produce an allergic reaction. Extremely flammable

aerosol. Pressurised container: May burst if heated. Harmful to aquatic life with long

lasting effects.

2.2. Label elements

Label elements:

Hazard statements: EUH208: Contains citral, limonene. May produce an allergic reaction.

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS02: Flame



POWER MAXED AIR-CON REFRESH (CITRUS)

Page: 2

Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.
P273: Avoid release to the environment.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122

°F.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ETHANOL

EINECS	CAS	PBT / WEL	CLP Classification	Percent	
200-578-6	64-17-5	Substance with a Community workplace exposure limit.	Flam. Liq. 2: H225	50-70%	
PETROLEUM	GASES, LIQUEF	IED			
270-704-2	68476-85-7	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	30-50%	
METHANOL					
200-659-6	67-56-1	-	Flam. Liq. 2: H225; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT SE 1: H370	<1%	
LIMONENE					
227-813-5	5989-27-5	-	Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 1: H410	<1%	
CITRAL					
226-394-6	5392-40-5	-	Skin Irrit. 2: H315; Skin Sens. 1: H317	<1%	

POWER MAXED AIR-CON REFRESH (CITRUS)

Page: 3

ALLYL ALCOHOL

203-470-7	107-18-6	-	Flam. Liq. 2: H225; Acute Tox. 3: H331;	<1%
			Acute Tox. 3: H311; Acute Tox. 3: H301;	
		Eye Irrit. 2: H319; STOT SE 3: H335;		
			Skin Irrit. 2: H315; Aquatic Acute 1:	
			H400	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water. Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Inhalation: No data available.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Extremely flammable. In combustion emits toxic fumes. Forms explosive air-vapour

mixture. Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of

ignition. If outside do not approach from downwind.

POWER MAXED AIR-CON REFRESH (CITRUS)

Page: 4

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Do not use equipment in clean-up procedure which may

produce sparks. Clean-up should be dealt with only by qualified personnel familiar with

the specific substance.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Do not handle in a confined space.

Smoking is forbidden. Use non-sparking tools. Avoid direct contact with the substance.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep away from sources of ignition. Keep container

tightly closed. Keep away from direct sunlight.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

ETHANOL

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1920 mg/m3	-	-	-

PETROLEUM GASES, LIQUEFIED

UK	1,750mg/m3	2,180mg/m3	-	-
----	------------	------------	---	---

METHANOL

UK 266 mg/m3 333 mg/m3	-	-
------------------------	---	---

ALLYL ALCOHOL

UK 4.8 mg/m3 9.7 mg/m3	-
------------------------	---

DNEL/PNEC Values

DNEL / PNEC No data available.

POWER MAXED AIR-CON REFRESH (CITRUS)

Page: 5

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Respiratory protection not required.

Hand protection: Chemically resistant gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Prevent from entering in public sewers or the immediate environment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol

Flash point°C: <23

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

POWER MAXED AIR-CON REFRESH (CITRUS)

Page: 6

Hazardous ingredients:

ETHANOL

IVN	RAT	LD50	1440	mg/kg
ORL	MUS	LD50	3450	mg/kg
ORL	RAT	LD50	7060	mg/kg

METHANOL

IVN	RAT	LD50	2131	mg/kg
ORL	MUS	LD50	7300	mg/kg
ORL	RAT	LD50	5628	mg/kg

CITRAL

IPR	RAT	LD50	460	mg/kg
ORL	MUS	LD50	6	gm/kg
ORL	RAT	LD50	4960	mg/kg

ALLYL ALCOHOL

IVN	MUS	LD50	78	mg/kg
ORL	MUS	LD50	96	mg/kg
ORL	RAT	LD50	64	mg/kg

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Inhalation: No data available.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Other information: Not applicable.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

POWER MAXED AIR-CON REFRESH (CITRUS)

Page: 7

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Recovery operations: Not applicable.

Disposal of packaging: Not applicable.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation

(EU) 2015/830

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH208: Contains citral, limonene. May produce an allergic reaction.

H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H225: Highly flammable liquid and vapour.

H229: Pressurised container: May burst if heated.

H301: Toxic if swallowed.

H311: Toxic in contact with skin.

H315: Causes skin irritation.

POWER MAXED AIR-CON REFRESH (CITRUS)

Page: 8

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H335: May cause respiratory irritation.

H370: Causes damage to organs.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The information presented herein is based on data considered to be accurate as of the date of this Safety Data Sheet (SDS). However, an SDS may not be used as a commercial specification sheet of manufacturer or seller, and no warranty or representation, expressed or implied, is made as to the accuracy or comprehensiveness of the foregoing data and safety information, nor is any authorisation given or implied to practice any patented invention without a license. In addition, no responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the material.