

# PRODUCT INFORMATION



## EUROLUB GEAR FLUIDE 8G

<b>Description/Applications:</b>	A very high graded automatic transmission fluid based on special selected base oils, with a high viscosity index. Formulated for the lubrication of 8HP transmissions.
----------------------------------	---

<b>Can be used with:</b>	VAG G 060 162 BMW 83222152426 Jaguar 02JDE 26444 Land Rover LR023288 Chrysler 68157995AA Fiat 9.55550-AV5
--------------------------	--

<b>Delivery:</b>	Art.-Nr. 376001	12 x 1 Liter	plastic bottle
	Art.-Nr. 376020	20 Liter	plastic canister
	Art.-Nr. 376060	60 Liter	hobbock
	Art.-Nr. 376208	208 Liter	drum
	Art.-Nr. 376000	1.000 Liter	IBC

### Technical Data:

Data	Unit	Method	EUROLUB GEAR FLUIDE 8G
Density at 15°C	kg/L	DIN 51 757	0,845
Viscosity at 40°C	mm <sup>2</sup> /s	DIN 51 562	25,80
Viscosity at 100°C	mm <sup>2</sup> /s	DIN 51 562	6,00
Colour	Visual		green

The data provided are subject to change. Operating rules of the manufacturer.

Characteristics are typical of current production data are subject to change.

This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH  
Freisinger Strasse 25-27  
D-85386 Eching bei München - Germany  
Tel. 0049(0)8165 / 9591 - 0, Fax 0049(0)8165 / 9591 - 20  
[www.eurolub.com](http://www.eurolub.com), [info@eurolub.com](mailto:info@eurolub.com)

print: 23.02.2016, made 23.02.2016

reference: STA2103, 11.02.2016

name: GEAR FLUIDE 8G PDS\_GB.docx

page 1 of 1