



Mobil Super™ 2000 X1 10W-40  
Mobil Passenger Vehicle Lube, Austria

Premium Semi-Synthetic Passenger Vehicle Motor Oil

## Product Description

Mobil Super™ 2000 X1 10W-40 is a semi-synthetic motor oil that provides long engine life and protection against sludge & wear.

## Features and Benefits

Mobil Super 2000 products are industry proven so you can trust you will get the performance you want from your vehicle. Mobil Super 2000 X1 10W-40 provides:

- Enhanced sludge prevention
- Excellent engine cleanliness
- Excellent high temperature protection
- Excellent wear protection
- Good cold start-up performance

## Applications

Mobil Super 2000 products are formulated to give you confidence of protection beyond that of conventional oils. ExxonMobil recommends Mobil Super 2000 X1 10W-40 if you occasionally experience demanding driving conditions:

- Older engine technologies
- Gasoline and Diesel without Diesel Particulate Filters (DPF)
- Passenger cars, SUV's, light trucks and vans
- Highway cruising and stop and go city driving
- Normal to occasionally severe operating conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

## Specifications and Approvals

<b>Mobil Super 2000 X1 meets or exceeds the requirements of:</b>	<b>10W-40</b>
ACEA A3/B3	X

API SL	X
AAE (STO 003) Group B5	X

<b>Mobil Super 2000 X1 has the following builder approvals:</b>	<b>10W-40</b>
MB-Approval 229.1	X
VW 501 01/505 00	X
AVTOVAZ LADA cars	X

<b>Mobil Super 2000 X1 is recommended by ExxonMobil for use in applications requiring:</b>	<b>10W-40</b>
API CF	X

## Typical Properties

<b>Mobil Super 2000 X1</b>	
Viscosity	10W-40
cSt @ 40°C	97
cSt @ 100°C	14.4
Sulfated Ash, wt%, ASTM D 874	0.91
Phosphorous	0.144
Flash Point, °C, ASTM D 92	230
Density @15° C kg/l, ASTM D 4052	0.87
Pour Point, °C, ASTM D 97	-30

## Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet, or will be

provided by seller to customers if and as legally required. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Mobil Super are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

ExxonMobil Lubricants & Specialties Europe, division of ExxonMobil Petroleum & Chemicals BVBA.

This information relates only to products supplied in Europe (including Turkey) and the Former Soviet Union.

EXXONMOBIL LUBRICANTS & SPECIALTIES EUROPE, A DIVISION OF EXXONMOBIL PETROLEUM & CHEMICAL, BVBA (EMPC)

POLDERDIJKWEG

B-2030 Antwerpen

Belgium

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

© Copyright 2003-2016 Exxon Mobil Corporation. All Rights Reserved.