# **Technical Data Sheet**

Revised: 2015/08/07(version 1.0)

# PETRONAS Syntium Racer X1 10W-60



## **APPLICATIONS**

Suitable for all types of high-powered racing engines, passenger cars including gasoline and diesel engines and latest high performance cars fitted with fuel injections, multi-valves, turbochargers or superchargers operating under most severe conditions.

Note: Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

## SPECIFICATIONS & APPROVALS\*

Meets or Exceeds the	API SL/CF, ACEA A3/B3/B4
requirements of:	AFI SL/CF, ACEA AS/DS/D4

<sup>\*</sup> All technical data is provided for reference only.

## TYPICAL PHYSICAL DATA\*\*

Parameters	Method	Unit	Typical	
			Value	
Appearance	-	-	B&C	
Density 15°C	ASTM D 4052	g/cm <sup>2</sup>	0.862	
Viscosity @100°C	ASTM D 445	cSt	23.1	
Vicosity Index	ASTM D 2270	-	180	
Flash Point CI. O. C	ASTM D 92	$^{0}$ C	>200	
TBN	ASTM D 2896	mg KOH/g	9.9	
Pour Point	ASTM D 97	$^{0}$ C	<-36	
Foam @24°C	ASTM D 892	cc/s	Traces/0	
** These characteristics are typical of current production. Whilst future production will conform to PLI's				

<sup>\*\*</sup> These characteristics are typical of current production. Whilst future production will conform to PLI's specification, variations in these characteristics may occur.

# FEATURES & BENEFITS

- Ultimate power output & performance.
- Excellent protection in all extreme driving conditions.
- Effective in keeping engine cleanliness.
- Maintaining oil pressure at high speed.
- Excellent start-up under the most extreme conditions, allowing fast response and acceleration.

#### **OIL TYPE**

• Synthetic

#### Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refers to product SDS or contact us at: www.pli-petronas.com

#### Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contains herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortuous action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.

Code: 1808